



Technical Parameters			
Material	Die-cast Aluminium	Flow Rates	4.0 NM <sup>3</sup> /min
Rate/Max. Working Pressure	0.7 / 1.6MPa	Weight	17.5kg
Max. Working Temp.	66°C (ACS:30°C)	Min. Working Temp.	15°C

NO.	Purpose	Pipe Size	Connection Dimension			
a	Inlet	3"	Rc 3"			
b	Outlet	3"	Rc 3"			
c	Drain	1/2"	Rc 1/2"			

  

Purpose	Grade	AO	AA	AX	AR	AAR	ACS
Micro Rating (µm)		1	0.01	0.01	1	0.01	-
Residual Oil Mist Content (ppm)		0.5	0.01	0.001	-	-	0.003
Dry Pressure Drop (KPa)		7	10	20	7	10	7
Wet Pressure Drop (KPa)		14	20	40	-	-	-

Revision		Description		Signature	Date
Rev.	ECN NO.				
B					
C					
D					

  

Designed/Date	Checked/Date	Approved/Date	Material	Part No	Title
HI 20200611		KF 20200612	N/A	N/A	Filter 0620G

  

<b>PMS</b> Gas process Engineering		Projection	Size	Scale	Weight	Drinking No.
			A4	N/A	N/A Kg	NES-0620G/V2

  

Rev.	A
Sheet	1 of 1